

STEEL INJECTION PACKERS

HIGH-PERFORMANCE INJECTION PACKERS

ADCOS STEEL INJECTION PACKERS are designed to meet the needs of all ADCOS Injection Resins.



USES

ADCOS STEEL INJECTION PACKER is designed to meet the requirements for all ADCOS hydrophobic, hydrophilic, acrylate and geotechnical injection resins

ADVANTAGES

- 1/2" x 4"
- 3/8" x 4"
- Small diameters are less likely to hit rebar when drilling

TECHNICAL DATA

Physical Property	Method	Result
Material	N/A	Steel
Diameter	N/A	1/2" & 3/8"
Length	N/A	4"
Pressure Rating	N/A	3,300 P.S.I.

INSTRUCTIONS

Drill the appropriate size hole for the selected injection packer size. Once drilled in the desired location and depth, clean the injection port hole with out compressed air or water. Now insert the injection packer in the cleaned hole and to the correct depth so that the rubber gasket is sitting at least 1" below the substrate surface. Finally tighten the injection packer so that the rubber gasket compresses enough to hold it in place and contain the injection resin being pumped.

PACKAGING

x50 Per Package

STORAGE & SHELF LIFE

Store in a covered dry area between 40°F and 90°F. Shelf life is approximately 10 years after the production date if stored properly in the original, unopened and undamaged packaging.

SAFETY & HEALTH PRECAUTIONS

Always use protective clothing, gloves and goggles that meet the requirements with OSHA regulations. Avoid eye and skin contact. Do not ingest.

DISCLAIMER

All information is provided in good faith. Please note that the application, use, and processing of these products are beyond our control. Therefore, ADCOS cannot be held responsible for the results obtained or any associated damage. Depending on the evolution of knowledge and techniques, ADCOS reserves the right to change the composition and conditions of use of its products without prior notice. This technical data sheet supersedes all previous versions.